

1501 West 178th Street | Gardena, CA. 90248 310-767-7812 | 800-359-5679 | fax: 310-767-7836 info@matsui-color.com | www.matsui-color.com

Infinity Color Series - Mixing System

Technical Data Sheet

- Wet Ink Tack | Good
- After Flash Tack | Good
- **Printability** | Excellent •
- Surface Appearance | Matte •
- **Opacity/Viscosity** Med/Med
- Bleed Resistance | None •
- Flash Temperature | 160°F • (71°C)/decreases with deposit thickness
- Cure Temperature | 320°F (160°C)
- Squeegee Hardness | ٠ Medium
- Squeegee Blade | Sharp
- Squeegee Angle | 45 degrees ٠ to screen
- Squeegee Speed | Medium
- Underlay | N/A
- Emulsion | Direct or indirect •
- Mesh Count | 110-230 mc in • (43-90 mc cm)
- Thinner | RV Additive •
- Thickener | Thickener B .
- **Storage** | 65°F to 95°F (18°C • to 35°C). Avoid direct sun.
- Cleanup | Water and mild • soap or detergent
- Color Range | Various
- Substrate Type | Cotton and **Cotton Poly blends**
- Substrate Color(s) | Light, Medium and Dark Fabrics

Description

Infinity Color Series is a color mixing system in which all the colors in the system are ready for use or can be mixed into each other to make other colors. The best feature of this system, is you can follow the formulas in your color guide book without needing to use a software, making it the quickest and most economical way to make custom colors.

Available colors:

WB0366 Yellow 012 WB0367 Orange 021 WB0368 Warm Red WB0369 Rubine Red

WB0371 Purple WB0372 Medium Purple WB0377 Green WB0373 Violet WB0374 Dark Blue WB0370 Rhodamine Red WB0375 Reflex Blue

WB0376 Process Blue WB0378 Black WB0379 Spot Black WB0380 Trans White

Features

- Easy to mix and print
- Add up to 3% Fixer WF-N to improve wash fastness
- Excellent for 100% cotton, blends, and Polyester (with Under Base Blocker)
- Excellent printability with no viscosity modifications •
- Extremely soft hand feel that PVC inks cannot achieve ٠
- Is "PVC Free" and environmentally safe
- Can be printed wet-on-wet

Application

•

Print through mesh up to 230 mc in (90 mc cm) and cure at 320°F (160°C).

Special Recommendations

Infinity Colors should be mixed in clean vessels using clean mixing blades and utensils. Any contamination from other ink sources or non-approved additives could make Infinity Colors test positive for restricted PVC's.

- Use Retarder MG 1-3% to help with open time in the screen
- Use Fixer WF-N 1-3% to help with wash fastness ٠
- Use Softener MG 1-5% to help penetrate in to the garment
 - Use Fixer L 1-3% with low curing fabrics or electric dryers