



## Safety Data Sheet acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

### 1 Identification

- **Product identifier**
- **Trade name:** Printers Choice Hardener
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
River City Graphic Supply  
9311 Metric STE B  
Austin, Texas 78758  
512-454-0505  
  
info@rivercitygraphicsupply.com
- **Information department:** Product safety department
- **Emergency telephone number:** INFOTRAC 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
hydrochloric acid
- **Hazard statements**  
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**  
P260 Do not breathe dusts or mists.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 2)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· <b>Dangerous components:</b>	
7647-01-0	hydrochloric acid
	1-10%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

US

(Contd. on page 3)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

Trade name: **Printers Choice Hardener**

(Contd. of page 2)

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

For large spills: Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

7647-01-0	hydrochloric acid	1.8 ppm
-----------	-------------------	---------

- **PAC-2:**

7647-01-0	hydrochloric acid	22 ppm
-----------	-------------------	--------

- **PAC-3:**

7647-01-0	hydrochloric acid	100 ppm
-----------	-------------------	---------

### 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:** Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 3)

**· Control parameters****· Components with limit values that require monitoring at the workplace:****7647-01-0 hydrochloric acid**PEL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppmREL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppmTLV Ceiling limit value: 2.98 mg/m<sup>3</sup>, 2 ppm**· Additional information:** The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Tightly sealed goggles

US

(Contd. on page 5)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 4)

**9 Physical and chemical properties****· Information on basic physical and chemical properties****· General Information****· Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	According to product specification
<b>· Odor:</b>	Characteristic
<b>· Odor threshold:</b>	Not determined.

**· pH-value at 20 °C (68 °F):** <1**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	85 °C (185 °F)

**· Flash point:** Not applicable.**· Flammability (solid, gaseous):** Not applicable.**· Decomposition temperature:** Not determined.**· Auto igniting:** Product is not selfigniting.**· Danger of explosion:** Product does not present an explosion hazard.**· Explosion limits:**

<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.

**· Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)**· Density at 20 °C (68 °F):** 1.03 g/cm<sup>3</sup> (8.59535 lbs/gal)**· Relative density** Not determined.**· Vapor density** Not determined.**· Evaporation rate** Not determined.**· Solubility in / Miscibility with****Water:** Fully miscible.**· Partition coefficient (n-octanol/water):** Not determined.**· Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

**· Solvent content:****VOC content:** 0.0 g/l / 0.00 lb/gal**· Other information** No further relevant information available.**10 Stability and reactivity****· Reactivity** No further relevant information available.

(Contd. on page 6)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 5)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with alkali (lyes).
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**  
Strong caustic effect.  
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

7647-01-0 hydrochloric acid

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 6)

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

· **Uncleaned packagings:**

· **Recommendation:**

Dispose of content and/or container in accordance with local, regional, national and/or international regulations

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN1760

· **UN proper shipping name**

· **DOT**

· **IMDG**

· **IATA**

Corrosive liquids, n.o.s. hydrochloric acid

CORROSIVE LIQUID, N.O.S. HYDROCHLORIC ACID

CORROSIVE LIQUID, N.O.S. HYDROCHLORIC ACID

· **Transport hazard class(es)**

· **DOT, IMDG, IATA**



· **Class**

8 Corrosive substances

· **Label**

8

· **Packing group**

· **DOT, IMDG, IATA**

III

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Corrosive substances

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 7)

· <b>Danger code (Kemler):</b>	80
· <b>EMS Number:</b>	F-A,S-B
· <b>Segregation groups</b>	Acids
· <b>Stowage Category</b>	A
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1760 CORROSIVE LIQUID, N.O.S. HYDROCHLORIC ACID, 8, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

7647-01-0 hydrochloric acid

· **Section 313 (Specific toxic chemical listings):**

7647-01-0 hydrochloric acid

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 9)





## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 8)

**· New Jersey Special Hazardous Substance List:**

7647-01-0	hydrochloric acid	CO, RI
-----------	-------------------	--------

**· Pennsylvania Right-to-Know List:**

7647-01-0	hydrochloric acid
-----------	-------------------

**· Pennsylvania Special Hazardous Substance List:**

7647-01-0	hydrochloric acid	E
-----------	-------------------	---

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**· TLV (Threshold Limit Value established by ACGIH)**

7647-01-0	hydrochloric acid	A4
-----------	-------------------	----

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**· Hazard pictograms**

GHS05

**· Signal word** *Danger***· Hazard-determining components of labeling:**

hydrochloric acid

**· Hazard statements**

H314 Causes severe skin burns and eye damage.

**· Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/05/2019

Reviewed on 08/31/2017

**Trade name: Printers Choice Hardener**

(Contd. of page 9)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** H.S.D

· **Date of preparation / last revision** 03/05/2019 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1