

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

084-004 **Product number**

Product name Super Flash Spray Adhesive

Effective date 07-May-2009 Sprayway, Inc. **Company information** 1005 Westgate

Addison, IL 60101 United States

General Assistance 1-630-628-3000 Company phone

800-424-9300 **Emergency telephone US Emergency telephone outside US** 703-527-3887

05 Version #

19-Dec-2008 Supersedes date

2. Hazards Identification

Emergency overview Aerosol. EXTREMELY FLAMMABLE. Irritating to eyes, respiratory system and skin.

CONTENTS UNDER PRESSURE. Pressurized container may explode when exposed to

heat or flame.

Prolonged exposure may cause chronic effects.

Potential health effects

Contact may irritate or burn eyes. Eye contact may result in corneal injury. **Eyes**

Prolonged or repeated contact can result in defatting and drying of the skin which may Skin

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Central nervous system. Respiratory system. **Target organs**

Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss **Chronic effects**

of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Heptane	142-82-5	30 - 40
Acetone	67-64-1	20 - 30
Propane	74-98-6	10 - 15
n-Butane	106-97-8	8 - 10
Pentane	109-66-0	3 - 5
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

trade_name

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, Ingestion

> have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Product #: 084-Super Flash Spray Adhesive

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Protective equipment and precautions for firefighters

Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2). Do not use water.

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

Components	CAS#	TWA	STEL	Ceiling
Heptane	142-82-5	400 ppm	500 ppm	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Pentane	109-66-0	600 ppm	Not established	Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Heptane	142-82-5	500 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Pentane	109-66-0	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection

Wear chemical goggles.

Skin protection

Wear appropriate chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

9. Physical & Chemical Properties

Appearance Boiling point

Compressed liquefied gas. 91.4 °F (32.8 °C) estimated

trade_name MSDS US

Color Tan.

Flammability (HOC) 43.7151 kJ/g estimated

Flash back

-156 °F (-104.4 °C) estimated Flash point

Form Aerosol. Solvent. Odor Not applicable pН

Physical state Liquid.

35 - 45 @ 70F **Pressure**

None Solubility

Specific gravity 0.7078 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.

Conditions to avoid Heat, flames and sparks. May include oxides of nitrogen. **Hazardous decomposition products**

11. Toxicological Information

Acute effects Acute LD50: 39024 mg/kg estimated, Rat, Dermal

> Acute LC50: 261 mg/l/4h estimated, Rat, Inhalation Not expected to be hazardous by OSHA criteria.

Sensitization Reproductive effects Not expected to be hazardous by OSHA criteria. **Teratogenicity** Not expected to be hazardous by OSHA criteria.

12. Ecological Information

LC50 216 mg/L, Fish, 96.00 Hours, **Ecotoxicity**

EC50 48000 mg/L, Daphnia, 48.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions Contents under pressure. Do not allow this material to drain into sewers/water supplies. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose in

accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306 Packaging non bulk 156, 306 Packaging bulk None

trade_name MSDS US

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class2.1UN number1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region Inventory name On inventory (yes/no)* China Inventory of Existing Chemical Substances in China (IECSC) No Europe European Inventory of New and Existing Chemicals (EINECS) No Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone 67-64-1 Environmental hazard Heptane 142-82-5 Present

 Heptane
 142-82-5
 Present

 n-Butane
 106-97-8
 Present

 Pentane
 109-66-0
 Present

 Propane
 74-98-6
 Present

trade_name MSDS US

16. Other Information

HMIS® ratings Health: 2*

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Product and Company Identification: Product and Company Identification

Physical & Chemical Properties: Physical & Chemical Properties Transport Information: Product Shipping Name/Packing Group

trade_name MSDS US