Technical Data Sheet

n. 09 [February 2023]

Gyroscopic Mixers

COROB CLEVERmix 700E

v02

BASE FEATURES

| Туре | Gyroscopic mixer | corob |
|--------------------------------------|--|-------|
| Clamping function | Automatic [Pre-set or automatically selected] | |
| Plate positioning after mixing cycle | Automatic | |
| Mixing time (min) | Automatic [depends on can size]. Manual set from 30 s to 20 m [up to 40 m with tech configuration] | |
| Mixing speed [rpm] (*) | Pre-set or automatically selected [Variable customization possibiliti | es] |
| Mixing motor power [hp] (kW) | 0.75 (0.55) | |
| Working cycle | Continuous | |
| Mixing direction | Bi-directional | |
| Lower plate | Extractable | |

VERSIONS

| Panels | Sheet Metal |
|-----------|--|
| Door type | Sliding Shutter [default], Hinge door or Automatic vertical sliding door |

CAN HANDLING FEATURES

| Type of cans | Round / Square / Oval | |
|--------------------------------|--|--|
| Minimum can height [mm] (in) | 100 (3.9) / 89 (3.5) using the can adaptor | |
| Maximum can height [mm] (in) | 470 (18.5) | |
| Maximum can diameter [mm] (in) | 390 (15.4) | |
| Maximum can weight [kg] (lbs) | 40 (88) | |

POWER SUPPLY / MACHINE ENVIRONMENT

| Power supply [V] | Single phase; 200-240±10% (with autotransformer 100/110/127V; at 200V power reduction applies) |
|--|--|
| Frequency [Hz] | 50/60 |
| Fuses | F 10 A |
| Maximum power absorption [W] | 1050 |
| Working temperature [Celsius] (Fahrenheit) | From 10° to 40° (50° to 104°) |
| Relative humidity | From 5% to 85% (without condensation) |
| Noise level [dB(A)] | < 70 |
| Certification | CE/UKCA - ETL |
| | |

OVERALL DIMENSIONS

| OVERALE DIFICIONS | | |
|--|-------------|--|
| Length [mm] (in) | 805 (31.7) | |
| Depth [mm] (in) | 782 (30.8) | |
| Height [mm] (in) | 1112 (43.8) | |
| Footprint [m ²] (ft ²) | 0.63 (6.78) | |
| Machine Weight [kg] (lbs) | 163 (360) | |
| Machine + packaging Weight [kg] (lbs) | 188 (415) | |
| | | |

EQUIPMENT FEATURES

| Can handle holding hooks | Optional |
|--------------------------------------|---|
| Magnetic upper clamping plate | Optional |
| Non-extractable lower clamping plate | Optional [reduces the max can height to 410 mm] |
| Door lock during the complete cycle | Optional |
| Height risers | Optional |

^{*} Mixing speed can vary in function of weight, can shape and base paint characteristics. Take note: data refers to base configuration machine, figures may vary according to different specifications.

© COPYRIGHT 2023, COROB S.p.A. - All rights reserved in all countries
This information is provided without warranty, representation, inducement or license of any
kind. It is accurate to the best COROB's knowledge or is obtained from sources believed to
be accurate. COROB therefore assumes no legal responsibility for reliance upon given
information.



